



Hot Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

Stainless-steel coil skin

to withstand the elements

provides extra durability

(790SS & 795SS)

Electric / Belt Drive

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

Simple, easy-to-use control panel includes adjustable thermostat with precision safety controls

5 HP, 230V, 1PH electric motor (795SS) comes with thermal overload protection and manual reset

YEAR WARRANTY pump In HOTSY PUMPS limited

Hotsy-designed Triplex pumps carry a 7-year limited warranty

Convenient hose-reel bracket accepts swivel or stationary reels for ease in hose maneuverability and storage (optional on gas fired models)

> Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

Pneumatic tires for easy maneuvering

Model 795SS: 3.5 GPM @ 2000 PSI; Oil fired; 230V, 1PH; Belt Drive Pump



Heater coil carries a 5-year warranty

50-ft. length of high-pressure hosefor ease in cleaning
around a large area

Adjustable high pressure detergent injection ensures high-pressure sudsing for better cleaning

FEATURES

■ 3.0 to 3.5 GPM@2000 PSI

37-ft. power cord with safety Ground Fault Circuit Interrupter(GFCI breaker)

- Oil Fired
- 208V or 230V, 1PH
- Belt Drive Pump

700 SERIES Hot-Water ELECTRIC Models

Oil Fired

■ 3.0 to 3.5 GPM @ 1500 to 2000 PSI

■ Hotsy 7-Year Pump Warranty

■ Belt Drive

Designed for tough, industrial cleaning.

SPECIFICATIONS BELT or DIRECT D												DRIVE
MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	BTU/HR	PUMP	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
790SS	3.0	2000	4TEFC	230/1	20	Oil	289,900	Hotsy Triplex	Belt	Std	37"Lx28"Wx45.5"H	460
795SS	3.5	2000	5	230/1	24	Oil	289,900	Hotsy Triplex	Belt	Std	37"Lx28"Wx45.5"H	500
795SS-208	3.5	2000	5	208/1	27	Oil	289,900	Hotsy Triplex	Belt	Std	37"Lx28"Wx45.5"H	500

SS=Stainless Steel

DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly

oes a long way.

concentrated, so a little goes a long way.

HOTSY SOLUTION SELECTOR What's the best detergent for your next job? Find out with our solution selector. Scan this QR code or visit HOTSY.com

SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.



OPTIONS for 700 SERIES

8" Oil-Fired Draft Dampener (Models 790SS & 795SS) barometric; prevent backdrafts; keeps cold air out

PARTS & ACCESSORIES

Your local Hotsy dealer would be happy to provide an onsite demonstration to determine which pressure washer accessories will help speed cleaning and lower your costs. Hotsy dealers stock thousands of pressure washer replacement parts such as high pressure hose, trigger guns, high pressure nozzles, pumps, engines, motors, unloaders, filters and wands. In addition, you'll find a number of accessories designed to speed cleaning, the most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high





Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631 www.Hotsy.com email: info@Hotsy.com P/N 8.914-224.0/HOT_700 Effective 01/2

FIND OUT MORE ONLINE: HOTSY.COM

P/N 8.914-224.0/HOT_700 Effective 01/20 Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified. A member of KÄRCHER North America © 2020 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at $\pm 10\%$ and in some cases are tighter within $\pm 5\%$ of listed specifications.